Process Solutions

EP2 Hose Pump

- Max flow: 2.1 gpm (7.9 lpm)
- Ideal for chemical metering applications

EP3 Hose Pump

- Max flow: 6.2 gpm (23.6 lpm)
- Typically used for chemical metering & sanitary applications

EP4 Hose Pump

- Max flow: 19.5 gpm (73.8 lpm)
- Ideal for abrasive material transfer applications

Husky™ 205

- 1/4 in (6.3 mm) connection
- Max flow: 5 gpm (19 lpm)
- Polypropylene, acetal, PVDF

Husky 307

- 3/8 in (9.4 mm) connection
- Max flow: 7 gpm (26 lpm)
- Polypropylene, acetal

Husky 515

- 1/2 in (12.7 mm) connection
- Max flow: 15 gpm (57 lpm)
- Polypropylene, acetal, PVDF

Husky 716

- 3/4 in (19.1 mm) connection
- Max flow: 16 gpm (61 lpm)
- Aluminum, stainless steel

Husky 1050

- 1 in (25.4 mm) connection
- Max flow: 50 gpm (189 lpm)
- Aluminum, polypropylene, conductive polypropylene, PVDF, stainless steel, hastelloy

Husky 1590

- 1-1/2 in (38.1 mm) connection
- Max flow: 90 gpm (340 lpm)
- Polypropylene, PVDF, aluminum, stainless steel

Husky 2150

- 2 in (50.8 mm) connection
- Max flow: 150 gpm (568 lpm)
- Polypropylene, PVDF, aluminum, stainless steel, iron

Husky 3300

- 3 in (76.2 mm) connection
- Max flow: 300 gpm (1135 lpm)
- Polypropylene, aluminum, stainless steel

1:1 Fast-Flo®

- Max flow: 5 gpm (19 lpm)
- UL options available

Priming Piston Ink Pump

- Enclosed, dual seal wet cup for longer seal life
- Runaway control with optional DataTrak™

Hydraulic Ink Pump

- Up to 3 times more efficient than pneumatic pumps
- Typical applications:
  - Letterpress inks
  - Lithographic inks

Hydra-Clean®

- High pressure cleaning and sanitizing
- Air-operated for hazardous or confined areas
- 10:1, 12:1, 23:1, 30:1 or 45:1 ratio options
- Available in wall, cart or drum mount packages

877.84GRACO (1-877-844-7226) or visit us at www.graco.com/process

There are NO EQUALS

PROVEN QUALITY. LEADING TECHNOLOGY.

SaniForce®

Air-Operated Double Diaphragm Pumps

- Maximum flow rates to 150 gpm (567 lpm)
- Tri-clamp connections
- Fluid pressure up to 120 psi (8.4 bar, 0.84 MPa)
- Durable, lube-free non-sticking air valve

High Sanitation Diaphragm Pumps

- Maximum flow rates to 150 gpm (567 lpm)
- Durable, lube-free non-sticking air valve
- Interchangeable flapper and ball checks

3A High Sanitation Diaphragm Pumps

- Maximum flow rates to 150 gpm (567 lpm)
- Fluid pressure up to 120 psi (8.4 bar, 0.84 MPa)
- Quick knockdown design for easy cleaning and draining
- Interchangeable flapper and ball checks
- Leak detection

Bin Evacuation Systems™ (BES)

- Evacuate materials from 300 gallon (1,135 l) containers without adding water
- Inflatable wiper seals for increased efficiency and faster change-out of bins
- Available with two sanitary diaphragm pumps or up to four sanitary piston pumps
- Pneumatic or electronic control options

Piston Pumps

- Fluid transfer and supply of low to medium viscosity fluids
- Flow rates ranging from 1.5 to 14 gpm (5.7 to 53 lpm)
- Double-ball and priming piston designs

Drum Unloaders

- Unload materials from straight-sided or tapered drums
- Inflatable wiper seals for increased efficiency and faster change-out of drums
- Liner guard to prevent bags from entering pump
- Sanitary flange clamps for quick disassembly

877.84GRACO (1-877-844-7226) or visit us at www.gracosaniforce.com

unleash the POWER

©2013 Graco Inc. Form No. 340264 Rev. F 06/13 Printed in the U.S.A.

PROVEN QUALITY. LEADING TECHNOLOGY.